



GLX TRANSPARENCY VIEWERS



GLX viewers are precisely balanced to provide strict compliance with the photographic and graphic arts D5000 standard.

The ergonomic design of these viewers permits fast and easy relamping. They include a convenient transparency holder and an integrated handle that provide easy portability. In addition to convenient wall-mounting, these GLX viewers have an optional stand which adjusts to varied viewing angles, allowing the units to lay flat, stand vertically or incline at approximately 15 or 75°. They can be mounted on the wall as well.

Graphiclite 100

Every GTI® color viewing system features Graphiclite® 100 color viewing lamps. To ensure optimum viewing conditions, these lamps are manufactured with a unique blend of fluorescent phosphors. Unequaled by any other 5000° Kelvin lamp in the industry, the Graphiclite 100 produces a true full-spectrum white light, rendering colors with the highest degree of accuracy and efficiency. In GTI viewers, the Graphiclite 100 color viewing lamp produces an actual system CRI approaching 95.

Lamp Monitoring System



LiteGuard® II features an exclusive digital circuitry design. It emits a dynamic visual signal when the viewer:

- Requires relamping
- Has warmed up and stabilized
- Reaches 25, 50 and 100% of the critical color life of the lamps
- Experiences a significant voltage drop

Optional Light Dimming

Model GLX-3044 can be fitted with an optional dimming feature that incorporates electronic dimming ballasts, allowing the user to control the light intensity for an optimum match to a computer monitor for soft proofing applications.

Benefits

- Full-spectrum Graphiclite 100 color viewing lamps
- Non-glare Plexiglas® viewing surface
- Unique chrome grip
- Optional LiteGuard II viewing system monitor
- Optional dimming feature for soft proofing on model GLX-3044

Specifications

Model	Viewing Area	Operation at 120 volts/60Hz	Net Weight	Gross Weight
GLX-3044	30x42"/76x107cm	202 Watts	67 Lbs./30 kg	77 Lbs./35 kg
GLX-3856	38x56"/96x142cm	294 Watts	108 Lbs./50 kg	120 Lbs./54 kg
GLX-4856	47x56"/119x142cm	378 Watts	135 Lbs./61 kg	150 Lbs./68 kg